

Cuivre Copper ASTM B837	Dia. Ext. Out. Dia.	Pi./Roul. Ft/Coil
749-005	1/8	50 '
749-010	3/16	50 '
749-015	1/4	50 '
749-020	5/16	50 '
749-025	3/8	50 '
749-038	7/16	50 '
749-030	1/2	50 '
749-035	5/8	50 '
749-204	3/8	100 '
749-205	1/2	100 '
749-206	5/8	100 '



Aluminium	Dia. Ext. Out. Dia.	Pi./Roul. Ft/Coil
749-050	1/8	50 '
749-055	3/16	50 '
749-060	1/4	50 '
749-064	5/16	50 '
749-065	3/8	50 '
749-068	7/16	50 '
749-070	1/2	50 '
749-075	5/8	50 '

Cuivre gainé Coated Copper ASTM B837	Dia. Ext Out. Dia.	Pi./Roul. Ft/Coil
749-230	3/8"	50'
749-231	3/8"	60'
749-232	3/8"	100'
749-233	3/8"	250'
749-234	1/2"	50'
749-235	1/2"	60'
749-236	1/2"	100'
749-237	1/2"	250'
749-238	5/8"	50'
749-239	5/8"	60'
749-240	5/8"	100'
749-241	5/8"	250'
749-242	3/4"	100'
749-180 Étiquettes Labels	"Gaz Propane" "Propane Gas" 250 pcs	



Cuivre gainé ASTM B837
Type "G" pour installation souterraine.

Coated copper tubing ASTM B837 for
underground type "G" gas installations.